

# RISING TERRA UNIVERSAL BOLLARD



The HVM Rising Bollard has been successfully impact tested to the International IWA 14 specification stopping 7.2t @ 50mph (80mph). The easy glide Bollard is fully automatic and hydraulically driven. Interchangeable sleeves available to match the static HVM Terra Bollards.

- IWA 14 Terra Universal Bollard 7.2t @ 80kph
- V/7200[N2A]/80/90:6.3

Tested dimensions: lift height 1000mm, diameter 245Ø

## BENEFITS & FEATURES

- Successfully impact tested to IWA14
- Easy glide, hydraulically driven
- Outstanding 360° Hostile Vehicle Mitigation protection from the threat of VBIED's (vehicle borne improvised explosive devices)
- Designed to complement our Planet range of Static Bollard heights and diameters; interchangeable sleeves are fitted to the inner bollard core, creating a versatile and stylish perimeter protection solution.
- 30% less steel than its predecessor with a visibly reduced footprint & attractive hexagonal plate
- Designed for ease of installation with a simple fabric mesh pocket.
- Designed for ease of maintenance
- Instantly reversible, 100% duty rated motor
- Control cabinet recommended to be installed within 10 metres of unit

## OPERATING SPEED

- Typical speeds of 4-6 seconds\*
- EFO (extra fast operation) in up to 1-2 seconds

## OPTIONS

- Accumulator or manual hand pump allow a number of operations in power failure mode
- In the event of Power Failure options of Fail Secure or Fail Safe
- High Security Cabinet
- Can be interfaced to any access control systems
- 100mm LED Traffic Light System

## SAFETY

- Vehicle detector loops
- Safety Photocell Beams, Light Curtain, Ultra-sonic Sensors and Lasers

## CIVIL REQUIREMENTS

L: 1200 x W: 1200 x D: 1515

Note: Power and control wiring ducts may be required

Control Cabinet Foundation (millimetres)  
L: 800 x W: 800 x D: 300

## ELECTRICAL REQUIREMENTS\*\*

- Three Phase Supply

\* Depending on configuration

\*\* This is subject to a risk assessment to ensure the automatic equipment complies to BS EN 12453

