



TERRA

Earth

Bollard

7.2t @ 80kph

FEATURES

- Crash Tested to the latest ISO regulation
- Crash Rating: Tested to withstand the impact of a 7.2 ton vehicle at 80 kph
- Finish: HDG (Hot-Dip Galvanized) and epoxy coated as standard
- Optional Sleeves: Available in a range of finishes, including stainless steel
- Equivalent to PAS68, 1 meter penetration.
- Applications: Ideal for protecting high-security entrances, data centers, energy facilities, airports, and other critical infrastructure



SPECIFICATION

- Type: Root fixed for bollard with foundation type C.
- Height Above Ground: 1080 mm
- Diameter: 298 mm
- Top Style: Flat top (standard)
- Installation: Root fixed with rebar reinforcement
- Impact Performance: Tested in the UK by MIRA 1778 kJ impact energy
- Finish Options: Shot blasted, hot zinc sprayed, or galvanized
- Colour: Painted to any RAL colour (Available color in warehouse RAL7024-Graphite Grey)
- Testing: Tested as one unit.

CONTACT US

-  00971 2 621 2272
-  www.fpgulf.com
-  Office 1301, Building C88, Commercial Tower A, 15 Baghdad St, Abu Dhabi, UAE
-  sales@frontierpitts.ae



FRONTIER
PITTS
MIDDLE EAST